

Specifications

Specifications subject to change.

Table 1. 245U-E-A1 specifications

Specification	Description
Transmitter and receiver	
Frequency	5.150 - 5.825 GHz ①
Transmit power	15–630 mW (country-specific)
Transmission modulation	Direct sequence spread spectrum (DSSS) ① Orthogonal frequency data modulation (OFDM) ①
Receiver sensitivity	–95 dBm at 6 Mbps; –74 dBm at 108 Mbps (8% FER) ①
Channel spacing	20 MHz spacing (27 channels,) ①
Data rate	6–108 Mbps ① “Auto Mode” selects fastest rate possible relative to RSSI
Range (LoS)	9 miles (15 km) ①
Antenna connector	1 x female SMA, standard polarity
Input and output	
Discrete I/O	Input voltage-free contact ③ Output FET 30 Vdc 500 mA ③
Ethernet port	
Ethernet port	100Base-T, RJ-45 connector–IEEE 802.3
Link activity	Link, 100Base-T via LED
Serial port	
RS-232	DB-9 female DCE, RTS/CTS/DTR/DCD
RS-485	2-pin terminal block, non-isolated ④
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400 bps
Serial settings	7/8 data bits, stop/start/parity (configurable)
Protocols and configuration	
System address	ESSID; 1–31 character text string
Protocols supported	TCP/IP, UDP, ARP, SNMP, RADIUS/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TFTP, TELNET, Modbus and Modbus-TCP
User configuration	User configurable parameters via HTTPS embedded Web server
Configurable parameters	Access point/client/bridge/router/VLAN Point to point, point to multipoint Wireless distribution system (AP–AP repeater) Modbus TCP/RTU gateway Serial client/server/multicast Simultaneous RS-232/RS-485 connection Embedded Modbus master/slave for I/O transfer
Security	Data encryption, 802.11i with CCMP 128-bit AES Support for 802.1x Radius server Secure HTTP protocol
Bandwidth protection	MAC address; whitelist/blacklist IP filtering; whitelist/blacklist ARP/GARP filtering; whitelist/blacklist
LED indication and diagnostics	
LED indication	Power/OK, RX, TX/link, RS-232, LAN, RS-485, digital I/O status Refer to product manual for further information
Reported diagnostics	RSSI measurements, connectivity information/statistics, log file
Network management	Optional network management system

① Frequency range dependent on country of model.

② Typical maximum line of sight range, RF Power dependent.

③ Can be used to transfer I/O status or communications failure output.

④ Maximum distance: 3937 ft (1200 m).

Table 1. 245U-E-A1 specifications, continued

Specification	Description
Compliance	
EMC	FCC Part 15; EN 301 489–17; AS/NZS CISPR22
RF (radio)	EN 301 893; FCC Part 15; RSS 210
Hazardous area	CSA Class I, Division 2; ATEX; IECEx nA IIC
Safety	IEC 60950 (RoHS compliant)
UL®	UL Listed
General	
Size	4.5 in x 5.5 in x 1.2 in (114 mm x 140 mm x 30 mm)
Housing	Powder-coated aluminum
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 14 AWG 0.1 in ² (2.5 mm ²)
Temperature rating	–40 to +140 °F (–40 to +60 °C)
Humidity rating	0–99% RH noncondensing
Weight	1.0 lb (0.45 kg)
Power supply	
Nominal supply	9 to 30 Vdc, under/overvoltage protection
Average current draw	270 mA at 12 V (idle); 140 mA at 24 V (idle)
Transmit current draw	470 mA at 12 V (400 mW), 250 mA at 24 V (600 mW)

Product selection

Table 2 245U-E-A1 accessories

Description	Product code
Antennas 5.8 GHz	
Collinear antenna, N-type female, 6-dBi gain, mounting bracket	COL5806
Collinear antenna, N-type female, 10-dBi gain, mounting bracket	COL5810
Cables	
Coaxial cable kit, 9.8 ft (3 m)/32.8 ft (10 m)/65.6 ft (20 m), N-type to SMA	CC3/10/20-SMA
Coaxial cable tail, 1.97 ft (600 mm), SMA to N-type female/male	CCTAIL-SMA-F/M
Ethernet cable, 6 ft (1.8 m), crossover, RJ-45 to RJ-45	ETH-C5X
Ethernet cable, 6 ft (1.8 m), direct, RJ-45 to RJ-45	ETH-C5A
Surge diverters	
SMA surge diverter for use with CC10/CC20-SMA	CSD-SMA-2500
Coaxial surge diverter, bulkhead N-female to N-female	CSD-N-6000
Power supply surge diverter, 110 Vac/15 A	MA15/D/1/S1
Power supplies	
DIN rail power supply, 100–250 Vac, 12 Vdc/2.5 A	PS-DINAC-12DC-0K
DIN rail power supply, 85–264 Vac, 24 Vdc/2.5 A	PS-DINAC-24DC-0K
Mounting brackets	
Mounting bracket kit for collinear antenna	BR-COL-KIT

Table 3. 245U-E-A1 ordering

Description	Frequency	RF power	Product code
Ethernet 802.11a	5.8GHz DSSS	630 mW	EL-245U-E-A1-AU
Ethernet 802.11a	5.8GHz DSSS	630 mW	EL-245U-E-A1-US
Ethernet 802.11a	5.8GHz DSSS	100 mW	EL-245U-E-A1-EU



ELPRO Technologies

9/12 Billabong Street
Stafford Queensland 4053 Australia

Telephone:
Global: +61 7 3352 8600
USA: +1 855 443 5776

sales@elpro.com.au
www.elpro.com.au

© 2018 ELPRO Technologies
All Rights Reserved
Publication No. EL-245U-E-A1
November 2018

ELPRO Technologies is a registered
trademark.

All other trademarks are property
of their respective owners.