

# 245U-E-G1 wireless Ethernet modem

## 802.11 wireless Ethernet for reliable long-distance connectivity



The ELPRO 245U-E-G1 is a cost-effective and robust solution to enable your devices for the Internet of Things (IoT) and Industrie 4.0. With an easy to access 802.11 wireless network, the 245U-E-G1 allows your devices to communicate through the industry-standard 2.4 GHz frequency band used by most devices. The 245U-E is a cost-effective and robust Ethernet modem, with industry-leading transmit power and industrial ratings.

### Applications

- Factory automation and safety interlocks
- Networking wind turbines and solar collectors
- Video surveillance
- Automated vehicle control
- Tank farm monitoring

### Description

The ELPRO 245U-E-G1 wireless Ethernet modem is a robust, inexpensive, license-free wireless 802.11 standards-compliant transceiver capable of high-bandwidth communications. Operating at 2.4 GHz and up to 630 mW, the ELPRO 245U-E-G1 is optimized for data rates of up to 108 Mbps, providing robust long-distance and secure two-way wireless communications in challenging environments typical of industrial monitoring and control applications.

Capable of operating in access point/client configuration, functioning as a network bridge/router, or serving as a serial server (RS-232/RS-485), the ELPRO 245U-E-G1 offers node-to-node deterministic mesh network repeatability for greater range and multiple channel spacing options to increase network scalability. Integrated Modbus® server capability allows seamless I/O expansion through the use of ELPRO 115S expansion modules or third-party modbus devices.

### Features

- 802.11b/g standard-compliant options
- 2.412–2.472 GHz frequency (802.11b/g) and 15–630 mW RF power
- Up to 108 Mbps data rate support
- 13-channel (802.11b/g) support
- Single antenna connection for easy installation
- Access point/client and bridge/router configuration
- Serial client/server/multicast Modbus TCP to RTU gateway
- 10/100Base-T IEEE® 802.3 Ethernet
- Spanning tree (self-healing) support
- Deterministic AP-to-AP mesh network repeatability
- Fast roaming for AP-to-AP handover
- IEEE 802.11i secure 128-bit AES encryption (WPA2)
- MAC and IP address filtering
- Digital I/O channel transfer
- Configurable settings for high-noise environments
- Over-the-air network diagnostics and configuration
- VLAN tagging support for bridging and routing modes

**EAT•N**

Powering Business Worldwide

## Specifications

Specifications subject to change.

**Table 1. 245U-E-G1 specifications**

Specification	Description
<b>Transmitter and receiver</b>	
Frequency	2.412–2.472 GHz ①
Transmit power	15–630 mW (data rate and country-specific)
Transmission modulation	Direct sequence spread spectrum (DSSS) ① Orthogonal frequency data modulation (OFDM) ①
Receiver sensitivity	–100 dBm at 250 kbps; –74 dBm at 108 Mbps (8% FER) ①
Channel spacing	5 MHz spacing (13 channels, 2.412–2.472 GHz) ①
Data rate	250 kbps–108 Mbps ① “Auto Mode” selects fastest rate possible relative to RSSI
Range (LoS)	9 miles (15 km) at 600 mW ①②
Antenna connector	1 x female SMA, standard polarity
<b>Input and output</b>	
Discrete I/O	Input voltage-free contact ③ Output FET 30 Vdc 500 mA ③
<b>Ethernet port</b>	
Ethernet port	100Base-T, RJ-45 connector–IEEE 802.3
Link activity	Link, 100Base-T via LED
<b>Serial port</b>	
RS-232	DB-9 female DCE, RTS/CTS/DTR/DCD
RS-485	2-pin terminal block, non-isolated ④
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400 bps
Serial settings	7/8 data bits, stop/start/parity (configurable)
<b>Protocols and configuration</b>	
System address	ESSID; 1–31 character text string
Protocols supported	TCP/IP, UDP, ARP, SNMP, RADIUS/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TFTP, TELNET, Modbus and Modbus-TCP
User configuration	User configurable parameters via HTTPS embedded Web server
Configurable parameters	Access point/client/bridge/router/VLAN Point to point, point to multipoint Wireless distribution system (AP–AP repeater) Modbus TCP/RTU gateway Serial client/server/multicast Simultaneous RS-232/RS-485 connection Embedded Modbus master/slave for I/O transfer
Security	Data encryption, 802.11i with CCMP 128-bit AES Support for 802.1x Radius server Secure HTTP protocol
Bandwidth protection	MAC address; whitelist/blacklist IP filtering; whitelist/blacklist ARP/GARP filtering; whitelist/blacklist
<b>LED indication and diagnostics</b>	
LED indication	Power/OK, RX, TX/link, RS-232, LAN, RS-485, digital I/O status Refer to product manual for further information
Reported diagnostics	RSSI measurements, connectivity information/statistics, log file
Network management	Optional network management system

① Frequency range dependent on country of model.

② Typical maximum line of sight range.

③ Can be used to transfer I/O status or communications failure output.

④ Maximum distance: 3937 ft (1200 m).

**Table 1. 245U-E-G1 specifications, continued**

Specification	Description
<b>Compliance</b>	
EMC	FCC Part 15; EN 301 489–17; AS/NZS CISPR22
RF (radio)	EN 300 328 ①; FCC Part 15; RSS 210
Hazardous area	CSA Class I, Division 2; ATEX; IECEx nA IIC
Safety	IEC 60950 (RoHS compliant)
UL®	UL Listed
<b>General</b>	
Size	4.5 in x 5.5 in x 1.2 in (114 mm x 140 mm x 30 mm)
Housing	Powder-coated aluminum
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 14 AWG 0.1 in <sup>2</sup> (2.5 mm <sup>2</sup> )
Temperature rating	–40 to +140 °F (–40 to +60 °C)
Humidity rating	0–99% RH noncondensing
Weight	1.0 lb (0.45 kg)
<b>Power supply</b>	
Nominal supply	9 to 30 Vdc, under/overvoltage protection
Average current draw	270 mA at 12 V (idle); 140 mA at 24 V (idle)
Transmit current draw	470 mA at 12 V (400 mW), 250 mA at 24 V (600 mW)

## Product selection

**Table 2. 245U-E-G1 accessories**

Description	Product code	Data sheet
<b>Antennas 2.4 GHz</b>		
Dipole antenna, 15 ft (4.6 m) cellfoil/SMA, 0-dBi gain, mounting bracket	<b>MD2400-EL</b>	<b>TD032053EN</b>
Collinear antenna, N-type, 5-dBi gain, mounting bracket	<b>SG2400-EL</b>	<b>TD032054EN</b>
Collinear antenna, N-type, 10-dBi gain, mounting bracket	<b>Z2400-EL</b>	<b>TD032054EN</b>
Yagi antenna, N-type, 18-dBi gain	<b>Y2400-18EL</b>	<b>TD032056EN</b>
Whip antenna: SMA male, 2-dBi gain, 2.1 in (54 mm)	<b>WH2400</b>	<b>TD032052EN</b>
<b>Cables</b>		
Coaxial cable kit, 9.8 ft (3 m)/32.8 ft (10 m)/65.6 ft (20 m), N-type to SMA	<b>CC3/10/20-SMA</b>	<b>TD032019EN</b> <b>TD032020EN</b> <b>TD032021EN</b>
Coaxial cable tail, 1.97 ft (600 mm), SMA to N-type female/male	<b>CCTAIL-SMA-F/M</b>	<b>TD032023EN</b>
Ethernet cable, 6 ft (1.8 m), crossover, RJ-45 to RJ-45	<b>ETH-C5X</b>	<b>TD032025EN</b>
Ethernet cable, 6 ft (1.8 m), direct, RJ-45 to RJ-45	<b>ETH-C5A</b>	<b>TD032024EN</b>
<b>Surge diverters</b>		
SMA surge diverter for use with CC10/CC20-SMA	<b>CSD-SMA-2500</b>	<b>TD032030EN</b>
Coaxial surge diverter, bulkhead N-female to N-female	<b>CSD-N-6000</b>	<b>TD032031EN</b>
Power supply surge diverter, 110 Vac/15 A	<b>MA15/D/1/S1</b>	<b>TD032029EN</b>
<b>Power supplies</b>		
DIN rail power supply, 100–250 Vac, 12 Vdc/2.5 A	<b>PS-DINAC-12DC-OK</b>	<b>TD032033EN</b>
DIN rail power supply, 85–264 Vac, 24 Vdc/2.5 A	<b>PSG60E</b>	<b>TD032034EN</b>
<b>Mounting brackets</b>		
Mounting bracket kit for collinear antenna	<b>BR-COL-KIT</b>	<b>TD032072EN</b>

**Table 3. 245U-E-G1 ordering**

Description	Frequency	RF power	Product code
Ethernet 802.11b/g	2.4 GHz DSSS	100/630 mW	<b>EL-245U-E-G1</b>

North America  
10955 SW Avery Street  
Tualatin, OR 97062  
United States  
Telephone: +1 800 845 6269

North America & Latin America  
5735 W. Las Positas Suite 100  
Pleasanton, CA 94588  
United States  
Telephone: +1 925 924 8500

Australia, New Zealand  
9/12 Billabong Street  
Stafford Queensland 4053  
Australia  
Telephone: +61 7 3352 8600

Europe  
Hein-Moeller-Straße 7-11  
53115 Bonn, Germany  
Telephone: +49 (0) 180 5223822

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

**Eaton's wireless business**  
[www.eaton.com/wireless](http://www.eaton.com/wireless)

© 2016 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. TD032102EN / Z18386  
July 2016



Eaton is a registered trademark.

All other trademarks are property  
of their respective owners.