













































WAGO cijene (Product Group 7 – Push Wire) vrijede od 10.06.2020.

Sve cijene su bez PDV-a.

Oznaka	Opis	Presjek (mm ²) i tip vodiča	Minimalna narudžba (kom)	Cijena KN / 1 kom	Cijena KN / 1 kom (manje kol)
 221-412	COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	1,38	1,79
 221-413	COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	1,76	2,29
 221-415	COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	2,75	3,58
 221-500	Mounting carrier; 221 Series - 4 mm ² ; for DIN-35 rail mounting/screw mounting; orange	-----	100	3,60	4,68
 221-612	COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	2000	2,60	3,38
 221-613	COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	2100	3,14	4,08
 221-615	COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	1000	5,28	6,86
 221-510	Mounting carrier; 221 Series - 6 mm ² ; for DIN-35 rail mounting/screw mounting; orange	-----	50	5,23	8,70
 222-412	CLASSIC Splicing Connector; for all conductor types; max. 4 mm ² ; 2-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	1,30	1,69
 222-413	CLASSIC Splicing Connector; for all conductor types; max. 4 mm ² ; 3-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	1,61	2,09
 222-415	CLASSIC Splicing Connector; for all conductor types; max. 4 mm ² ; 5-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	2,60	3,38
 222-500	Mounting carrier; 222 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	2,83	3,68

	222-505	Strain relief plate; for mounting carrier; 221 or 222 Series, can be snapped	-----	100	1,91	2,48
	222-510	Angled DIN-rail adapter; in combination with mounting carrier; 221-500 or 222-500; for DIN-35 rail mounting; gray	-----	100	1,91	2,48
	224-101	Power supply connector; 105 °C; gray	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	1000	1,23	1,87
	224-104	Power supply connector; 120 °C; black	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,49	2,37
	224-112	Power supply connector; 105 °C; white	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	1000	1,23	1,87
	224-114	Power supply connector; 120 °C; black	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,67	2,67
	224-201	Power supply connector; gray	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	50	2,91	4,55
	243-112	Mounting carrier; for 4 connectors; 243 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	1,38	1,79
	243-113	Mounting carrier; for 6 connectors; 243 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	1,45	1,89
	243-144	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; transparent housing; light gray cover; Surrounding air temperature: max 60°C; transparent	Ø 0.4 - 0.5 mm (puna)	1000	0,92	1,20
	243-204	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; dark gray housing; light gray cover; Surrounding air temperature: max 60°C; dark gray	Ø 0.6 - 0.8 mm (puna)	1000	0,92	1,20
	243-208	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; dark gray housing; light gray cover; Surrounding air temperature: max 60°C; dark gray	Ø 0.6 - 0.8 mm (puna)	500	1,45	1,89

	243-304	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray housing; light gray cover; Surrounding air temperature: max 60°C; light gray	Ø 0.6 – 0.8 mm (puna)	1000	0,92	1,20
	243-308	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray housing; light gray cover; Surrounding air temperature: max 60°C; light gray	Ø 0.6 – 0.8 mm (puna)	500	1,45	1,89
	243-504	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray cover; Surrounding air temperature: max 60°C; yellow	Ø 0.6 – 0.8 mm (puna)	1000	0,92	1,20
	243-508	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray cover; Surrounding air temperature: max 60°C; yellow	Ø 0.6 – 0.8 mm (puna)	500	1,45	1,89
	243-804	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray cover; Surrounding air temperature: max 60°C; red	Ø 0.6 – 0.8 mm (puna)	1000	0,92	1,20
	243-808	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray cover; Surrounding air temperature: max 60°C; red	Ø 0.6 – 0.8 mm (puna)	500	1,45	1,89
	2273-202	COMPACT splicing connector; for solid conductors; max. 2.5 mm ² ; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,54	0,70
	2273-203	COMPACT splicing connector; for solid conductors; max. 2.5 mm ² ; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,61	0,79
	2273-204	COMPACT splicing connector; for solid conductors; max. 2.5 mm ² ; 4-conductor; transparent housing; red cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,84	1,09
	2273-205	COMPACT splicing connector; for solid conductors; max. 2.5 mm ² ; 5-conductor; transparent housing; yellow cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,84	1,09
	2273-208	COMPACT splicing connector; for solid conductors; max. 2.5 mm ² ; 8-conductor; transparent housing; light gray cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	500	1,45	1,89
	2273-500	Mounting carrier; for single- and double-row con.; 2273 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	3,14	4,08

	773-602 PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm ² ; 2-conductor; Brown clear housing; white cover; Surrounding air temperature: max 60°C	1.5 - 4 (puna)	1000	1,07	1,39
	773-604 PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm ² ; 4-conductor; Brown clear housing; red cover; Surrounding air temperature: max 60°C	1.5 - 4 (puna)	1000	1,53	1,99
	773-606 PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm ² ; 6-conductor; Brown clear housing; brown cover; Surrounding air temperature: max 60°C	1.5 - 4 (puna)	500	1,91	2,48
	773-332 Mounting carrier; 773 Series - 2.5 mm ² / 4 mm ² / 6 mm ² ; for DIN-35 rail mounting/screw mounting; orange	-----	50	2,30	2,99
	773-173 PUSH WIRE® connector for junction boxes; for solid and stranded conductors; max. 6 mm ² ; 3-conductor; transparent housing; red cover; Surrounding air temperature: max 60°C	2.5 - 6 (puna)	500	1,91	2,48
	887-910 Splicing Connector Set; T-BOXX®; 222, 224, 243, 2273 Series	2.5, 4 (puna, licnasta)	1	1.519,21	-----
	887-912 Splicing Connector Set; T-BOXX®; 221, 2273, 773, 224, 243 Series	2.5, 4 (puna, licnasta)	1	1.695,47	-----
	887-913 Splicing Connector Set; L-BOXX® 102; 221, 2273, 773, 224, 243 Series	2.5, 4, 6 (puna, licnasta)	1	1.695,47	-----