














## WAGO cijene (Product Group 7 – Push Wire) vrijede od 01.10.2021.

Sve cijene su bez PDV-a.

Oznaka	Opis	Presjek (mm <sup>2</sup> ) i tip vodiča	Minimalna narudžba (kom)	Cijena KN / 1 kom	Cijena KN / 1 kom (manje kol)
 221-412	COMPACT Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	1,49	2,27
 221-413	COMPACT Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	1,92	2,80
 221-415	COMPACT Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.2 – 4 (puna, licnasta)	1000	3,06	4,37
 221-500	Mounting carrier; 221 Series - 4 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; orange	-----	100	3,93	5,24
 221-612	COMPACT Splicing Connector; for all conductor types; max. 6 mm <sup>2</sup> ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	2000	2,88	4,02
 221-613	COMPACT Splicing Connector; for all conductor types; max. 6 mm <sup>2</sup> ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	2100	3,50	4,81
 221-615	COMPACT Splicing Connector; for all conductor types; max. 6 mm <sup>2</sup> ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); transparent	0.5 – 6 (puna, licnasta)	1005	5,77	8,04
 221-510	Mounting carrier; 221 Series - 6 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; orange	-----	10	7,69	7,69
 222-412	CLASSIC Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	1,49	2,10
 222-413	CLASSIC Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 3-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	1,75	2,54
 222-415	CLASSIC Splicing Connector; for all conductor types; max. 4 mm <sup>2</sup> ; 5-conductor; with levers; gray housing; Surrounding air temperature: max 40°C; gray	0.08 – 2.5 (puna) 0.08 – 4 (licnasta)	1000	2,88	4,20
 222-500	Mounting carrier; 222 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	3,06	4,46



222-505 Strain relief plate; for mounting carrier; 221 or 222 Series, can be snapped

-----

100

2,10

3,15



222-510 Angled DIN-rail adapter; in combination with mounting carrier; 221-500 or 222-500; for DIN-35 rail mounting; gray

-----

100

2,10

3,15



221-2401 Inline splicing connector with lever; for all conductor types; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 85°C (T85); transparent

0,2 - 4 (puna)  
0,5 - 2,5 (licnasta)

60

2,71

2,71



221-2411 Inline splicing connector with lever; for all conductor types; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); transparent

0,2 - 4 (puna)  
0,5 - 2,5 (licnasta)

60

2,71

2,71



221-2501 Mounting carrier with strain relief; 1-way; for inline splicing connector with lever; for screw mounting; gray

-----

5

3,85

3,85



221-2502 Mounting carrier with strain relief; 2-way; for inline splicing connector with lever; for screw mounting; gray

-----

5

4,20

4,20



221-2503 Mounting carrier with strain relief; 3way; for inline splicing connector with lever; for screw mounting; gray

-----

5

4,81

4,81



221-2504 Mounting carrier with strain relief; 4-way; for inline splicing connector with lever; for screw mounting; gray

-----

5

5,42

5,42



221-2505 Mounting carrier with strain relief; 5-way; for inline splicing connector with lever; for screw mounting; gray

-----

5

5,86

5,86



221-2511 Mounting carrier with strain relief; 1-way; for inline splicing connector with lever; with snap-in mounting foot; gray

-----

5

3,85

3,85



221-2512 Mounting carrier with strain relief; 2-way; for inline splicing connector with lever; with snap-in mounting foot; gray

-----

5

4,55

4,55















221-2513 Mounting carrier with strain relief; 3-way; for inline splicing connector with lever; with snap-in mounting foot; gray













-----














5







5,16

5,16

	221-2514	Mounting carrier with strain relief; 4-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	5,60	5,60
	221-2515	Mounting carrier with strain relief; 5-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	6,12	6,12
	221-2521	Mounting carrier; 1-way; for inline splicing connector with lever; for screw mounting; gray	-----	5	3,50	3,50
	221-2522	Mounting carrier; 2-way; for inline splicing connector with lever; for screw mounting; gray	-----	5	3,85	3,85
	221-2523	Mounting carrier; 3-way; for inline splicing connector with lever; for screw mounting; gray	-----	5	4,37	4,37
	221-2524	Mounting carrier; 4-way; for inline splicing connector with lever; for screw mounting; gray	-----	5	4,63	4,63
	221-2525	Mounting carrier; 5-way; for inline splicing connector with lever; for screw mounting; gray	-----	5	5,16	5,16
	221-2531	Mounting carrier; 1-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	3,58	3,58
	221-2532	Mounting carrier; 2-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	4,02	4,02
	221-2533	Mounting carrier; 3-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	4,55	4,55
	221-2534	Mounting carrier; 4-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	4,98	4,98
	221-2535	Mounting carrier; 5-way; for inline splicing connector with lever; with snap-in mounting foot; gray	-----	5	5,42	5,42

	224-101	Power supply connector; 105 °C; gray	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,31	1,31
	224-104	Power supply connector; 120 °C; black	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,66	1,66
	224-112	Power supply connector; 105 °C; white	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,40	1,40
	224-114	Power supply connector; 120 °C; black	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	100	1,92	1,92
	224-201	Power supply connector; gray	1 - 2.5 (puna) 0.5 - 2.5 (licnasta)	50	3,23	3,23
	243-112	Mounting carrier; for 4 connectors; 243 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	1,49	2,27
	243-113	Mounting carrier; for 6 connectors; 243 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	1,66	2,40
	243-144	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; transparent housing; light gray cover; Surrounding air temperature: max 60°C; transparent	Ø 0.4 - 0.5 mm (puna)	1000	0,96	1,49
	243-204	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; dark gray housing; light gray cover; Surrounding air temperature: max 60°C; dark gray	Ø 0.6 - 0.8 mm (puna)	1000	0,96	1,49
	243-208	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; dark gray housing; light gray cover; Surrounding air temperature: max 60°C; dark gray	Ø 0.6 - 0.8 mm (puna)	500	1,57	2,27
	243-304	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray housing; light gray cover; Surrounding air temperature: max 60°C; light gray	Ø 0.6 - 0.8 mm (puna)	1000	0,96	1,49
	243-308	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray housing; light gray cover; Surrounding air temperature: max 60°C; light gray	Ø 0.6 - 0.8 mm (puna)	500	1,57	2,27

	243-504	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray cover; Surrounding air temperature: max 60°C; yellow	Ø 0.6 – 0.8 mm (puna)	1000	0,96	1,49
	243-508	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray cover; Surrounding air temperature: max 60°C; yellow	Ø 0.6 – 0.8 mm (puna)	500	1,57	2,27
	243-804	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 4-conductor; light gray cover; Surrounding air temperature: max 60°C; red	Ø 0.6 – 0.8 mm (puna)	100	0,96	1,49
	243-808	MICRO PUSH WIRE® connector for junction boxes; for solid conductors; 0.8 mm Ø; 8-conductor; light gray cover; Surrounding air temperature: max 60°C; red	Ø 0.6 – 0.8 mm (puna)	500	1,57	2,27
	2273-202	COMPACT splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,61	0,87
	2273-203	COMPACT splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 3-conductor; transparent housing; orange cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,70	0,96
	2273-204	COMPACT splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 4-conductor; transparent housing; red cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,87	1,40
	2273-205	COMPACT splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 5-conductor; transparent housing; yellow cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	1000	0,96	1,49
	2273-208	COMPACT splicing connector; for solid conductors; max. 2.5 mm <sup>2</sup> ; 8-conductor; transparent housing; light gray cover; Surrounding air temperature: max 60°C (T60); transparent	0.5 – 2.5 (puna)	500	1,57	2,27
	2273-500	Mounting carrier; for single- and double-row con.; 2273 Series; for DIN-35 rail mounting/screw mounting; orange	-----	100	3,41	4,81
	773-602	PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm <sup>2</sup> ; 2-conductor; Brown clear housing; white cover; Surrounding air temperature: max 60°C	1.5 – 4 (puna)	1000	1,14	1,66
	773-604	PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm <sup>2</sup> ; 4-conductor; Brown clear housing; red cover; Surrounding air temperature: max 60°C	1.5 – 4 (puna)	1000	1,66	2,45
	773-606	PUSH WIRE® connector for junction boxes; for solid conductors; max. 4 mm <sup>2</sup> ; 6-conductor; Brown clear housing; brown cover; Surrounding air temperature: max 60°C	1.5 – 4 (puna)	500	2,10	3,06

	773-332 Mounting carrier; 773 Series - 2.5 mm <sup>2</sup> / 4 mm <sup>2</sup> / 6 mm <sup>2</sup> ; for DIN-35 rail mounting/screw mounting; orange	-----	50	2,54	3,76
	773-173 PUSH WIRE® connector for junction boxes; for solid and stranded conductors; max. 6 mm <sup>2</sup> ; 3-conductor; transparent housing; red cover; Surrounding air temperature: max 60°C	2.5 – 6 (puna)	500	2,10	3,15
	887-952 Splicing Connector Set; L-BOXX® Mini; 100 x 221-412, 100 x 221-413, 25 x 221-415, 4 x 221-500	2.5, 4 (puna, licnasta)	1	662,84	662,84
	887-910 Splicing Connector Set; T-BOXX®; 100 x 2273-202, 100 x 2273-203, 100 x 2273-205, 50 x 2273-208, 50 x 222-413, 40 x 222-415, 100 x 224-101, 100 x 243-204, 100 x 243-804, 50 x 243-208, 10 x 243-113	2.5, 4 (puna, licnasta)	1	1.674,76	1.674,76
	887-912 Splicing Connector Set; T-BOXX®; 100 x 2273-203, 100 x 2273-205, 50 x 2273-208, 50 x 221-413, 25 x 221-415, 100 x 224-112, 100 x 773-604, 100 x 243-204, 100 x 243-804, 50 x 243-208, 10 x 243-113	2.5, 4 (puna, licnasta)	1	1.868,96	1.868,96
	887-925 Splicing Connector Set; L-BOXX® 102; 100 x 221-412, 50 x 221-413, 25 x 221-415, 100 x 224-112, 100 x 243-204, 50 x 243-208, 100 x 2273-203, 100 x 2273-205, 50 x 2273-208, 100 x 773-173, 4 x 221-500	2.5, 4, 6 (puna, licnasta)	1	2.031,53	2.031,53

Besplatne uzorke možete naručiti na [wago@microstar.hr](mailto:wago@microstar.hr)

Uzorke šaljemo poštom na teret naručitelja.

Raspoloživo u uzorcima su serije 222, 224, 2273, 243