

# 915U-2 Wireless Mesh Networking I/O and Gateway

**Long-range, scalable, industrial multiple I/O node and gateway**



## Description

The ELPRO 915U-2 Wireless Mesh Networking I/O and Gateway is a multiple I/O node that extends communications to sensors and actuators in local, remote, or difficult-to-reach locations. Designed with a long-range, license-free wireless transceiver, the 915U-2 can provide IP-based mesh networking across sprawling industrial environments typical of industrial applications.

Capable of ad-hoc mesh networking, roaming and discovery, as well as deterministic mesh, the 915U-2 can serve as an end node, a routing node, or a network gateway. Scalable to thousands of nodes, its gather-scatter and block mapping technology offers efficient utilization of network resources and eases integration into complex monitoring and control systems. Integrated Modbus® server capability allows further I/O expansion through the use of ELPRO 115S expansion modules.

The 915U-2XM is a factory hardware option that provides 200 MB of extended internal flash memory specifically for use with the logging soft feature key option. Soft feature options are available for the 915U-2 and 915U-2XM, including Modbus TCP and logging. These are purchased separately and can be enabled as required via a code provided.

## Features

- 902–928 MHz frequency hopping spread spectrum (FHSS) up to 1W RF Power
- 869 MHz wideband up to 500 mW for Europe
- Self-healing IP-based wireless mesh networking
- Multi-hop repeater and gateway functionality
- Gather-scatter and block mapping
- Serial client/server/multicast Modbus TCP to RTU gateway
- Configurable digital, pulse, and analog I/O to 14-bit resolution
- 10/100Base-T IEEE 802.3 Ethernet
- Secure 128-bit AES encryption
- Modbus RTU and TCP support
- Over-the-air network diagnostics and configuration
- Optional support for logging of register variables (see 915U-LOG data sheet)

## Applications

- Oil and gas production and distribution
- Pipeline monitoring and leak detection
- Mining operations infrastructure
- Water treatment facilities
- Water and wastewater systems

## Specifications

SPECIFICATION	DESCRIPTION
<b>Transmitter and Receiver</b>	
Frequency	902–928 MHz ①, 869.525 MHz, 869.875 MHz ①
Transmit power	1 mW (+0 dBm) to 1W (+30 dBm) ② 1 mW (+0 dBm) to 500 mW (+27 dBm) ③
Transmission	Frequency hopping spread spectrum (FHSS) ② Single frequency ③
Modulation	Frequency shift keying (FSK)
Receiver sensitivity	–109 dBm @ 19.2 kbps (3% FER) ② –109 dBm @ 14.4 kbps (3% FER) ③
Channel spacing	50 x 250 kHz ② ④, single 250 kHz ③
Data rate	19.2–115.2 kbps ① ②, 14.4–76.8 kbps ① ③
Range (LoS)	20 miles (32 km) @ 1W ② ⑤ 6 miles (10 km) @ 500 mW ③ ⑤
Antenna connector	1 x female SMA standard polarity



Powering Business Worldwide

## Specifications (continued)

SPECIFICATION	DESCRIPTION
<b>Input and Output</b>	
Discrete input	8 digital I/O (1–4 configurable as PI or PO) On-state voltage: <2.1 Vdc Wetting current: 5 mA Max. I/P pulse rate—DI 1/2: 50 kHz, DI 3/4: 1 kHz Max. I/P pulse width—DI 1/2: 10 µs, PI 3/4: 0.2 ms
Discrete output	8 digital I/O (1–4 configurable as PI or PO) On-state voltage—DO max.: 30 Vdc Wetting current—DO max.: 200 mA Max O/P pulse rate—PO max. rate: 1 kHz
Analog inputs	4 AI (2 differential, 2 single ended) Current range: 0–24 mA Current resolution: 14 bits Accuracy (current): 0.1% Voltage input range: AI 1/2: 0–25V, AI 3/4: 0–5V Voltage resolution: 14 bits Accuracy (voltage): 0.1%
Analog output	2 AO (sourcing) Current range: 0–24 mA Current resolution: 13 bits Accuracy (current): 0.1%
<b>Ethernet Port</b>	
Ethernet port	10/100Base-T, RJ-45 connector, IEEE 802.3
Link activity	Link, 100Base-T via LED
<b>Serial Port</b>	
RS-232	EIA-562 (R-45 connector)
RS-485	2-pin terminal block, non-isolated Ⓞ
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400
Serial settings	7/8 data bits, stop/start/parity (configurable)
<b>Protocols and Configuration</b>	
System address	ESSID, 1 to 31-character text string
Protocols supported	TCP/IP, UDP, HTTP, FTP, TFTP, TELNET, Modbus, Modbus TCP
User configuration	All user-configurable parameters via HTTPS
Configurable parameters	Unit details, I/O mappings and parameters, radio settings (for more information, refer to the user manual) Modbus TCP/ RTU gateway Embedded Modbus master/slave for I/O transfer
Security	Data encryption, 128-bit AES, secure HTTP protocol
<b>LED Indication and Diagnostics</b>	
LED indication	Power/OK, TX/RX, RS-232, RS-485, digital I/O, analog I/O status
Reported diagnostics	RSSI measurements (dBm), connectivity information/statistics, system log file
Network management	Optional network management system
<b>Compliance</b>	
EMC	FCC Part 15; EN 301 489; AS 3548
RF (radio)	FCC Part 15.247; EN 300 220; AS 4268.2; RFS29 NZ
Hazardous area	UL/CSA Class I, Division 2; ATEX; IECEx Na IIC
Safety	IEC 60950 (RoHS compliant)
UL	UL listed
<b>General</b>	
Size	5.91" x 7.09" x 1.38" (180 mm x 150 mm x 35 mm)
Housing	IP20 rated high-density thermoplastic
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 12 AWG 0.1 in. <sup>2</sup> (2.5 mm <sup>2</sup> )
Temperature rating	–40 to +140°F (–40 to +60°C)
Humidity rating	0–99% RH noncondensing
Weight	1.1lb (0.5 kg)

SPECIFICATION	DESCRIPTION
<b>Power Supply</b>	
Nominal supply	10.8–30 Vdc, under/over voltage protection
Average current draw	220 mA @ 12V (idle), 110 mA @ 24V (idle)
Transmit current draw	500 mA @ 12V (1W), 250 mA @ 24V (1W)

**Note:** Specifications are subject to change.

- Ⓐ Country-specific configuration (specified at time of order)
- Ⓑ 900 MHz ISM band
- Ⓒ 869 MHz ISM band (Europe)
- Ⓓ 18 channels New Zealand
- Ⓔ Typical maximum line-of-sight range
- Ⓕ Maximum distance 3937' (1200m)
- Ⓖ Optional, see 915U-TCP datasheet

## Accessories

PRODUCT CODE	DESCRIPTION	DATA SHEET
--------------	-------------	------------

### Soft Feature Keys

915U-TCP	Modbus TCP/RTU gateway feature key	TD032089EN
915U-LOG	Data logging feature key	TD032090EN

### Interface

915U-TCADP	T-type TCP thermocouple adapter, uses two analog inputs and two analog outputs	TD032088EN
------------	--	------------

### Antennas - 900 MHz

DG800-1/5	Whip antenna, SMA male, angle bracket, –2 dBi gain, 3' (1m) or 16.4' (5m) coaxial cable	TD032046EN
DG900-1/5		TD032047EN
CFD890EL	Dipole antenna, SMA male, mounting bracket, 2 dBi gain, 16' (5m) coaxial cable	TD032048EN
SG900EL	Collinear antenna, N-type female, 5 dBi gain	TD032049EN
SG900-6	Collinear antenna, N-type female, 8 dBi gain	TD032050EN

### Cables

ETH-C5A	Ethernet cable, 6' (1.8m), straight through, RJ-45 to RJ-45	TD032024EN
SER-RJ45	Configuration cable, RS-232 serial, DB-9 female to RJ-45	TD032027EN

### Surge Diverters

CSD-SMA-2500	SMA surge diverter for use with CC10/CC20-SMA	TD032030EN
CSD-N-6000	Coaxial surge diverter, bulkhead N female to N female	TD032031EN
MA15D1SI/D2SI	Power supply surge diverter, 110 Vac/15A or 240 Vac/15A	TD032029EN
IOP32D	Signal surge diverter, 2 x 2-wire/1 x 4-wire	TD032032EN

### Power Supplies

PS-DINAC-12DC-OK	DIN rail power supply, 100–250 Vac, 12 Vdc/2.5A	TD032033EN
PSG60E	DIN rail power supply, 85–264 Vac, 24 Vdc/2.5A	TD032034EN

**Notes:** More accessories are available for this product including antennas, cables, and mounting brackets. Refer to our Website for details.

## Ordering

PRODUCT CODE	DESCRIPTION	FREQUENCY	RF POWER
915U-2	Wireless mesh I/O	902–928 MHz	1W
915U-2	Wireless mesh I/O	869.525 MHz	500 mW
915U-2	Wireless mesh I/O	869.875 MHz	5 mW
915U-2XM	Wireless mesh I/O + 500 MB flash memory Ⓐ	902–928 MHz	1W
915U-2XM	Wireless mesh I/O + 500 MB flash memory Ⓐ	869.525 MHz	500 mW
915U-2XM	Wireless mesh I/O + 500 MB flash memory Ⓐ	869.875 MHz	5 mW

**Note:** Available RF power and frequency may vary depending on country of application.

Ⓐ Additional memory for logging of data and administration events

**Eaton's wireless business**

[www.eaton.com/wireless](http://www.eaton.com/wireless)

North America & Latin America  
5735 W. Las Positas Suite 100  
Pleasanton, CA 94588  
United States  
Telephone: +1 925 924 8500

Australia, New Zealand  
9/12 Billabong Street  
Stafford Queensland 4053  
Australia  
Telephone: +61 7 3352 8600

China  
955 Shengli Road  
East Area of Zhangjiang High-Tech Park  
Shanghai, 201201  
China  
Telephone: +86 21 2899 3600

Southeast Asia  
2 Serangoon North Avenue 5  
# 06-01 Fu Yu Building, 554911  
Singapore  
Telephone: +65 6645 9888

Europe  
Hein-Moeller-Straße 7-11  
53115 Bonn, Germany  
Telephone: +49 (0) 180 5223822

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
[Eaton.com](http://Eaton.com)

© 2014 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. TD032016EN  
January 2014



Eaton is a registered trademark.

All other trademarks are property of their respective owners.